


XBO 4000 W/DHP OFR

XBO DHP | Xenon short-arc lamps for digital cinema projection



Product datasheet

Technical data

Electrical data


Construction wattage	4.2 kW
Nominal wattage	4000 W
Nominal voltage	33 V
Nominal current	120.00 A
Current control range	100...130 A

Light technical data

Luminous intensity	19000 cd ¹⁾
Luminous flux	160000 lm

¹⁾ Measured in the vertical burning position

Dimensions & weight



Product line drawing

Diameter	60.0 mm
Length	295.0 mm

Lifespan

Lifespan	1100 h
----------	--------

Additional product data

Base (standard designation)	SFc27/SFaX27
Arc stability, horizontal	Yes
Picto Projection	Yes


Product datasheet

Capabilities

Burning position	s70/p20 ¹⁾
-------------------------	-----------------------

¹⁾ For vertical burning position: anode (+) on top

Product datasheet



Burning position

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (height x width x length)	Volume	Gross weight
4052899091825	XBO 4000 W/DHP OFR	Shipping carton box 1	- x - x -		

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disposal

The cold internal pressure of the lamp is approx. 8 bar of Xenon, the lamp must first be depressurized before it can be disposed. Place the lamp – in its protective jacket – in a plastic bag and drop it from a height of 1.0...1.5 m onto a hard surface (e.g. concrete).

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.