

Technical Information

No. 5466

Edition: 01/07

Substitutes: new

Status: valid

Xenon Short Arc Lamp

XBO® 2000 W/DTP OFR

■ Product description

The OSRAM XBO® 2000 W/DTP OFR. DTP stands for Digital Threaded Pin. Produced with the latest high brightness XBO technology. A new generation of high light output lamps specially developed for applications requiring excellent arc stability and maximum efficiency of its luminance.

■ Technical data

Order reference	XBO® 2000 W/DTP OFR	
Rated lamp wattage	W	2000
Rated lamp voltage	V	25
Rated lamp current (=)	A	80
Current control range	A	50 - 85
Ignition voltage	kV _s	33
Min. open circuit voltage for cold / hot ignition	V	75 / 100
Luminous flux	lm	80000
Luminous intensity	cd	7500
Average luminance	cd/cm ²	75000
Luminous area w x h *)	mm	1,3 x 4,0
Electrode gap e (cold)	mm	5.0
Lamp length (overall) L ₁	mm	max. 403
Lamp length L ₂	mm	max. 354
LCL a	mm	160
Bulb diameter d	mm	52
Average service life	h	3000
Warranty	h	2400
Base	Cathode: SFc 25-14 Anode: SFa 25-14	

*) w = luminance half width value; h = height of luminance area (corresponds to electrode gap, hot)

■ Lamp operation

Maximum permissible base temperature	°C	230
Cooling	Forced cooling fan	
Min. air flow velocity around discharge vessel	m/s	6
Magnetic arc stabilization	required in horizontal burning position	
Burning position	S 30 (vertical ± 30°; anode up) ; p 30 (horizontal ± 30°)	

