

Technical Information

No. 5543

Edition 01/07

Substitutes: new
Status: valid



Xenon Short Arc Lamp

XBO[®] 2000 W/H CL OFR

■ Product description

The OSRAM XBO[®] 2000 W/H CL OFR is a DC-operated lamp that is especially suited for applications requiring excellent arc stability and a high luminance. The CL lamps, which stands for Classic Line, combines the classical Osram features with an optimization on bulb pricing and has the same warranty as the regular standard lamps.

■ Technical data

Order reference	XBO [®] 2000 W/H CL OFR	
Rated lamp wattage	W	2000
Rated lamp voltage	V	28
Rated lamp current (DC)	A	70
Current control range	A	50 – 85
Ignition voltage	kV _P	33
Min. open circuit voltage for cold / hot ignition	V	85 / 110
Luminous flux	lm	80000
Luminous intensity	cd	7500
Average luminance	cd/cm ²	80000
Luminous area w x h *)	mm	1.3 x 4.8
Electrode gap e (cold)	mm	5,8
Lamp length (overall) l ₁	mm	max. 370
Lamp length l ₂	mm	max. 322
LCL a	mm	142,5
Bulb diameter d	mm	46
Warranty	h	2400
Base	Cathode	SFaX 27-12
	Anode	SFaX 27-10

*) w = luminance half width value; h = height of luminous area (corresponds to electrode gap, hot)

■ Lamp operation

Maximum permissible base temperature	230°C
Cooling requirements	forced cooling / fan necessary
Min. air flow velocity around discharge vessel	3 m/s
Operating position	s 30 (vertical ± 30°; anode up) ; p 30 (horizontal ± 30°)

